

DIFFERENTIAL PRESSURE GAUGE



Model summary

Model	Gauge Range	Model	Gauge Range
DPG60	0-60 Pa	DPG1k	0-1 kPa
DPG100	0-100 Pa	DPG1,5k	0-1,5 kPa
DPG120	0-120 Pa	DPG2k	0-2 kPa
DPG200	0-200 Pa	DPG3k	0-3 kPa
DPG250	0-250 Pa	DPG5k	0-5 kPa
DPG300	0-300 Pa	DPG ±30	30-0-30 Pa
DPG400	0-400 Pa	DPG ±60	60-0-60 Pa
DPG500	0-500 Pa	DPG ±120	120-0-120 Pa
DPG600	0-600 Pa	DPG ±250	250-0-250 Pa
DPG800	0-800 Pa	DPG ±500	500-0-500 Pa

Accessories

Standard accessories:

- 2 fixing screws
- 2 plastic duct connectors
- 2 m tube \varnothing 4 / 7 mm
- surface mounting plate

Optional accessories:

- metallic duct connectors (to be ordered separately)
- Flush mounting kit

Technical data

Materials	Housing	ABS
	Cover	PC
	Membrane	silicone
	Machinery	Aluminium and steel spring
Accuracy	$\pm 2\% \text{ F.S (20}^\circ\text{C)}$, (DPG60 <math>< \pm 4\%</math> ; DPG100 <math>< \pm 3\%</math>)	
Dial hole size	$\varnothing 110 \text{ mm}$	
Weight	234 grams	
Ambient conditions	Operation	-5... +60°C
	Storage	-40...+85°C
Please Note!	The rubber plug must be placed back to the hole after zero point setting	

Mounting position Vertical

Dimensions

